

5 KNUCKLE HALF MORTISE HINGES

Standard Weight Ball Bearing


FBB167 (ANSI A8212) – Steel – polished and plated or phosphated and prime coated for painting

FBB108 (ANSI A2212) – Brass or bronze – polished and plated or painted

FBB108 (32) (ANSI A5212) – Stainless steel – highly polished

FBB108 (32D) (ANSI A5212) – Stainless steel – satin finish

- For medium weight hollow metal or wood doors of average frequency, hung on channel iron frames
- Equipped with two Stanley permanently lubricated non-detachable ball bearings
- Pins in non-ferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)



Measurements below

Size Length of Joint	Width		Offset (C)	Gauge of Metal	Flat Head Machine Screws/Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)			Frame Leaf	Door Leaf			Bronze Lbs. (Kg)	Steel Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.134 (3.4)	3-12-24 X 1/2	3-12-24 X 1/2	3 EA.	30 EA.	30 (14)	29 (13)
5 (127)	1 1/2 (38.1)	2 1/16 (52.4)	7/16 (11.1)	.146 (3.7)	4-12-24 X 1/2	4-12-24 X 1/2	3 EA.	24 EA.	37 (17)	33 (15)